

## Waveguide / Guide d'onde

WR	WG	Frequency (GHz)
2300	00	0.32 – 0.49
2100	0	0.35 – 0.53
1800	1	0.41 – 0.62
1500	2	0.49 – 0.75
1150	3	0.64 – 0.96
975	4	0.75 – 1.12
770	5	0.96 – 1.45
650	6	1.12 – 1.7
510	7	1.45 – 2.20
430	8	1.7 – 2.6
340	9A	2.2 – 3.3
284	10	2.6 – 3.95
229	11A	3.3 – 4.9
187	12	3.95 – 5.85
159	13	4.90 – 7.05
137	14	5.85 – 8.2
112	15	7.05 – 10.0
90	16	8.2 – 12.4
75	17	10.0 – 15.0
62	18	12.4 – 18.0
51	19	15.0 – 22.0
42	20	18.0 – 26.5
34	21	22.0 – 33.0
28	22	26.5 – 40.0
22	23	33.0 – 50.0
19	24	40.0 – 60.0
15	25	50.0 – 75.0
12	26	60.0 – 90.0
10	27	75.0 – 110
8	28	90.4 – 140
6	29	110 – 170
5	30	140 – 220
4	31	170 – 260
3	32	220 – 325

### Double Ridge

WRD	Frequency (GHz)
WRD-200D24	2.0 – 4.8
WRD-250D30	2.6 – 7.8
WRD-350D24	3.5 – 8.2
WRD-475D24	4.75 – 11.0
WRD- 500D28	5.0 – 18.0
WRD-580D28	5.8 – 16.0
WRD-650D28	6.5 – 18.0
WRD-750D24	7.5 – 18.0
WRD-110C24	11.0 – 26.5
WRD-180C24	18.0 – 40.0